

**RFID tags and badges**

**PUCK ID**  
Ref. IDF2573



**Your heavy-duty Identification Tag to track all your assets**

- 👁️ High transmission range: **150 meters** (open field)
- 👁️ High lifecycle: up to **10 years**
- 👁️ Robust industrial case - **IP68** Waterproof
- 👁️ User-definable Tag's Identifier (RW)

**TECHNICAL SPECIFICATIONS**

Battery power supply	3,6 VDC – Li-SOCI2 Internal battery
Frequency	433.92 MHz
Radio frame format	24 bits or 32 bits
Settings & configuration	By SCIEL PROG IR tool and ERW configuration software
Max. transmission range	150m (open field under test conditions)
Indicative lifecycle	10 years (with transmission rate @2 seconds)
ID transmission cycle	From 220ms up to 10 hours by programming
Operating temperature	-40°C to +85°C
Battery level management	Specific ID code for low level of battery
Housing	<p>Ø 57mm base - Thickness 18mm</p> <p>IP68 Waterproof</p> <p>Weight 36g</p> <p>DELRIN (POM C) material</p> <p>– Food Grade (90/128/EEC)</p> <p>2 mounting Ø 4mm holes, spaced of 49mm</p>
Standards	<p>EN 301 489 – 3: 2013 V1.6.1;</p> <p>EN 300 220 – 2012: V2.4.1; EC; RoHS</p>
Accessory	PUCK HOLDER STICKER (ACIOM118)



**PUCK ID with its PUCK HOLDER STICKER**