

**RFID tags and badges**

**WATCH ID**

Ref. IDP2735 (white) – IDP2734 (blue)



- 👁️ User-definable Tag's Identifier (RW)
- 👁️ High receiving range: up to **80 meters** (open field)
- 👁️ Lifecycle: up to **10 years** (according to settings)
- 👁️ **IP68** Waterproof
- 👁️ Watch casing\*

**TECHNICAL SPECIFICATIONS**

Battery power supply	3 VDC – CR2032 Internal battery
Frequency	433.92 MHz
Operating temperature	-30°C to 70°C
Identifier settings	ID Code – Emission cycle – Activation/Deactivation
Duty cycle	From 0.22s up to 12hours by programming
Settings & configuration	By SCIEL PROG IR tool and ERW software
Reader's compatibility	SCIEL Reader Family
Battery level management	Specific ID code for low level of battery
Housing	Size: 45mm x 37mm – thickness 13mm Weight: 19g Material: Nylon Mounting: two loops 26mm x 2mm assemble the wristwatch
Standards	EN 301 489 – 3: 2002 V1.4.1 <sup>1</sup> ; EN 300 220 – 2007: V2.1.2; RoHS

<sup>1</sup> Except EN 61000-4-2 :1995 + A1:1998 + A2:2001.



\*Not supplied bracelet

