


TAG CHECKER

Ref: SCIBT60

Proximity Tester for Active RFID Tags



- 🕒 **Tester of active RFID tag's emissions and maintenance signal for battery's Tag low level**
- 🕒 **High lighting DELs and double tone Buzzer**
- 🕒 **Short range settings predefined in factory.**
- 🕒 **IP54 Waterproof ABS Housing**

Description :

The wall-mounted Tag CHECKER detects the tag or the card placed at a short distance from the CHECKER (< 20 cm). This setting is done in factory. The green DEL flashes at the same frequency as the emission's one of the tags and a buzzer is simultaneously activated. The red DEL flashes alternatively with the green DEL when the shown tag has reached the end of its autonomy (battery's Low Level). A buzzer with a different tone is simultaneously activated.

Specifications	
Power Supply	230Vac – Internal 12Vdc conversion board with fuse Power Supply Cable provided
Average current	20 mA @ 12Vdc
Frequency	433,92 MHz
Detection distance of Tags	Factory settings with short range < 20 cm
DEL Indicators	Green DEL and Buzzer Tone 1: tag's emission OK Red DEL and Buzzer Tone 2 : low level of tag's battery
Housing	ABS 180x 110 x 90 mm - IP54 Waterproof - 4 internal guided holes for wall mounting
Operating Temperature	-25° C to +60° C
Standards	EN 301 489 – 3 : 2002 V1.4.1 ; EN 300 220 – 2007 : V2.1.2 ; CE Mark ; RoHS Certified