

# Blue PUCK BUZZ+ Mesh

Industrial MESH 2.4Ghz location non-router Tag

## BENEFITS

- Simple deployment, maintenance, and expansion
- Smart battery management, very high autonomy : up to 20 years
- Pick to Light : high power integrated LED & Buzzer
- Smart & secure programming by NFC
- Over-the-air (OTA) firmware update via network



## TECHNICAL SPECIFICATIONS

### OPERATING MODE

<b>Frequency</b>	2.4 GHz – BLE channel / Mesh network
<b>Output power Range</b>	Up to +4 dBm (Smart network) Up to 140 meters open field (+4 dBm)
<b>Transmission period</b>	Setting of the 2 transmission periods (Moving state and static state), 15" to 18H.
<b>Radio frame format</b>	Setting of the 3-byte identifier, WIREPAS Network Address and Channel.  BLE Advertising Frame: Transmission Interval, Name and Power.* <i>*Refer to the frames specification for more information.</i>
<b>Settings and configuration</b>	Interface/protocol : NFC (Type 2) Acceleration level for inertial event wake up (can be set: 32 mg to 8000 mg) Network Configuration and Diagnostics: Wirepas Network Tool software
<b>Mobile beacon mode</b>	Periodic transmission of identifier and location data
<b>Anchor beacon mode</b>	Fixed point: fixed mesh network installation; data uploaded via network
<b>LED indicator and buzzer</b>	Controllable via network
<b>Sensor performance</b>	Location accuracy: 5 to 10 meters Accelerometer: Detection of inertial events (extended battery life) Range: -8g to 8g, Configurable threshold Buzzer: controllable via the network 4KHz/77dB at 8 cm

### BATTERY

<b>Power supply</b>	3 VDC - Internal lithium battery
<b>Battery life</b>	Up to 20 years Battery voltage level sent via network and on MQTT Topic* <i>*Refer to the battery life curves for more information.</i>

**CERTIFICATIONS**

<b>Europe</b>	CE : EN 300 328/EN 300 330, EN 301 489, EN 62311, EN 62368
<b>UK</b>	UKCA
<b>USA</b>	FCC : FCC PART 15
<b>Canada</b>	ISED : RSS-247/ICES-003
<b>RoHS</b>	Yes


**HOUSING**

<b>Dimensions</b>	Ø 57mm base – Height : 20mm
<b>Weight</b>	41g
<b>Materials</b>	DELTRIN (POM C) Compatible with food product (90/128/EEC)
<b>Waterproof grade</b>	IP65
<b>Operating temperature</b>	-40°C to +85°C

**ACCESSORIES**

<b>Tag support</b>	PUCK HOLDER STICKER (ACIOM 118B) PUCK HOLDER (ACIOM 117B) PUCK STICKER (ACIOM 188) 3M PT1100 - Ø 53mm – Thickness: 1,1mm
--------------------	-----------------------------------------------------------------------------------------------------------------------------------

**MECHANICAL DRAWINGS**



Blue PUCK BUZZ+ MESH

PUCK HOLDER

**AVAILABLE REFERENCES**

Ref	Description
IDF25454-01A	Blue Puck BUZZ + MESH STACK WP4 compatible & IP65
IDF25454-02A	Blue Puck BUZZ + MESH STACK WP4 compatible OPEN version
IDF25454-03A	Blue Puck BUZZ + MESH STACK WP5 compatible & IP65
IDF25454-04A	Blue Puck BUZZ + MESH STACK WP5 compatible OPEN version