

Blue ANCHOR

Industrial MESH 2.4GHz beacon

BENEFITS

- Simple deployment, maintenance, and expansion
- Very High autonomy: up to 15 years
- Pick to Light: integrated high power LED
- IP68 waterproof grade
- Over-the-air (OTA) firmware update via network



TECHNICAL SPECIFICATIONS

OPERATING MODE

Frequency 2.4 GHz – BLE channel / Mesh network

Output power Up to +4 dBm (Smart network)

Range Up to 100 meters open field (+4 dBm)

Transmission period Transmission periods 15" to 18H.

Radio frame format Setting of the 3-byte identifier, WIREPAS Network Address and Channel.

BLE Advertising Frame: Transmission Interval, Name and Power.*

*Refer to the frames specification for more information.

Settings and configuration Interface/protocol: NFC (Type 2)

Acceleration level for inertial event wake up (32 mg to 8000 mg)

Network Configuration and Diagnostics: Wirepas Network Tool software

Mobile beacon mode Periodic transmission of identifier and location data

Anchor beacon mode Fixed point: fixed mesh network installation; data uploaded wirelessly via

network

LED indicator Controllable via network

BATTERY

Power supply 3.6 VDC – Internal LS14500 lithium battery

Battery life

Τ°	Anchor	Mobile Beacon (position transmission		
		period)		
		1 min	5 min	10 min
+20°C	15 years	3 years	12 years	20 years
+70 °C	11 years	2 years	9 years	15 years
-40°C	8.5 years	1.5 years	5 years	9 years

Battery voltage level sent via network and on MQTT Topic* *Refer to the battery life curves for more information.



CERTIFICATIONS

Europe CE: EN 300 328/EN 300 330, EN 301 489, EN 62311, EN 62368

UK UKCA

USA FCC: FCC PART 15

Canada RSS-247 / ICES-003

RoHS Yes

HOUSING

Dimensions 119.2mm x 51.2mm x 24mm

Weight 122c

Materials DELRIN (POM C) Compatible with food product (90/128/EEC)

Waterproof grade IP68


Operating temperature -40°C to +85°C

ACCESSORIES

Tag sticker ANCHOR/LORA STICKER (ACIOM202)

3M PT1100 - 101.2 x 51.2mm - Thickness: 1,1mm

MECHANICAL DRAWINGS



AVAILABLE REFERENCES

Ref	Description
IDF32456-01A	Blue Anchor MESH STACK WP4 compatible & IP68 & 5,2Ah
IDF32456-02A	Blue Anchor MESH STACK WP5 compatible & IP68 & 5,2Ah