

# BLUE ANCHOR

## Industrial MESH 2.4GHz beacon



### BENEFITS

- Simple deployment, maintenance, and expansion
- Very High autonomy : up to 15 years
- Pick to Light : integrated high power LED
- IP68 waterproof grade
- Over-the-air (OTA) firmware update via network



## TECHNICAL SPECIFICATIONS

### OPERATING MODE

<b>Frequency</b>	2.4 GHz – BLE channel / Mesh network
<b>Output power</b> <b>Range</b>	Up to +4 dBm (configurable/ smart network) Up to 100 meters openfield (+4 dBm)
<b>Transmission period</b>	Transmission periods 15" to 18H.
<b>Radio frame format</b>	Setting of the 3-byte identifier, address and WIREPAS network channel. BLE Advertising Frame: Transmission Interval, Name and Power.* <i>*Refer to the frames specification for more information.</i>
<b>Settings and configuration</b>	Interface/protocol : NFC (Type 2) Acceleration level for inertial event wake up (32 mg to 8000 mg) Network Configuration and Diagnostics: Wirepas Network Tool software
<b>Mobile beacon mode</b> <b>Anchor beacon mode</b>	Periodic transmission of identifier and location data Fixed point: fixed mesh network installation; data uploaded wirelessly via network
<b>LED indicator</b>	Controllable via network

**BATTERY**

**Power supply** 3.6 VDC – Internal LS14500 lithium battery

**Battery life**

T°	Anchor	Mobile Beacon (position transmission period)		
		1 min	5 min	10 min
+20°C	15 years	3 years	12 years	20 years
+70 °C	11 years	2 years	9 years	15 years
-40°C	8.5 years	1.5 years	5 years	9 years

Battery voltage level sent via network and on MQTT Topic\*

*\*Refer to the battery life curves for more information.*

**CERTIFICATIONS**

**Europe** CE : EN 300 328/EN 300 330, EN 301 489, EN 62311, EN 62368

**USA** FCC : FCC PART 15

**Canada** RSS-247 / ICES-003

**RoHS** Yes

**HOUSING**

**Dimensions** 119.2mm x 51.2mm x 24mm

**Weight** 122g

**Materials** DELRIN (POM C) Compatible with food product (90/128/EEC)

**Waterproof grade** IP68

**Operating temperature** -40°C to +85°C

**ACCESSORIES**

**Tag sticker** ANCHOR/LORA STICKER (ACIOM202)  
3M PT1100 – 101.2 x 51.2mm – Thickness: 1,1mm

**MECHANICAL DRAWINGS**

