

BLUE PUCK MOV

Bluetooth Low Energy motion sensor



BENEFITS

- Integrated 3 axis accelerometer for Angular position & Motion measurement
- Very high autonomy : up to 20 years
- High transmission range
- Waterproof (IP68)
- Smart & secure programming by NFC
- Over The Air Programming (OTAP)



TECHNICAL SPECIFICATIONS

OPERATING MODE

Frequency 2,4 GHz - Bluetooth Low Energy 4.0/4.2
Output power Up to +4 dBm (paramétrable)
Range Up to 500 meters in open field (+4dBm)

Transmission period Advertising period (0,1 sec to 10 sec – configurable in seconds)

Radio frame format	Motion event detection (MOV)*	Angular position measurement (ANG)*
	Identifier (15 characters max) (15 bytes) Motion detection counter: Total number of motion events detected (2 bits) Motion instantaneous state (1bit)	Identifier (15 characters max) (15 bytes) X-axis acceleration (mg) (2 bytes) Y-axis acceleration (mg) (2 bytes) Z-axis acceleration (mg) (2 bytes)

**Refer to the frames specifications for more information*

Settings and configuration Interface/protocol: NFC (Type 2)

Connected mode Datalogger transmission (record of saved sensor data)
 Battery level command

Advertising mode Periodic sensors data transmission. Immediate transmission on change of sensor state

Sensors performance	Détecteur d'évènements inertiels (MOV)	Angular position measurement (ANG)
	Range: -8g to 8g Threshold level: between 32 mg and 8000 mg Motion event detector: Immediate transmission upon change of motion state	Range: -2g to 2g Resolution: 1mg (LSB) Accuracy: ±0,5% Full scale

BATTERY

Power supply	3 VDC - Internal lithium battery
Battery life	MOV = up to 20 years* ANG = up to 20 years* <i>* Refer to the battery life curves for more information</i>
Battery level	Low battery warning in advertising frames (<15%) Battery voltage in scan response frames (configurable)

CERTIFICATIONS

Europe	CE : EN 300 328/ EN 301 489 & EN 55032 / EN 62368-1
USA	FCC : FCC 15
Canada	ISED : RSS-247 / ICES-003
RoHS	Yes

HOUSING

Dimensions	Ø 57 mm base - Height 20 mm
Weight	41g
Materials	DELIRIN (POM C) Compatible with food products (90/128/EEC)
Waterproof grade	IP 68
Operating temperature	-40°C to +85°C

ACCESSORIES

Tag support	PUCK HOLDER STICKER (ACIOM118B) PUCK HOLDER (ACIOM117B) PUCK STICKER (ACIOM188) 3M PT1100 - Ø 53mm – Height: 1,1mm
--------------------	---

MECHANICAL DRAWINGS

