

## TAG CHECKER

Proximity tester for active RFID tags



### BENEFITS

- LED and Dual Tone Buzzer
- Short-distance pre-setting at the factory
- EMC: conforms to I-ETS 300-683 standard



## TECHNICAL SPECIFICATIONS

### OPERATING MODE

<b>Frequency</b>	433,92 MHz
<b>Detection range</b>	Factory set to short range <20cm
<b>Indicator</b>	Green LED and Buzzer TONE 1: emission OK Red LED and Buzzer TONE 2: Low battery tag

### POWER SUPPLY

<b>Power supply voltage</b>	Mains 230Vac - Internal 12 Vdc converter card with fuse - Mains cable
<b>Power supply current</b>	20mA @ 12Vdc

### CERTIFICATIONS

<b>Europe</b>	EN 300 220 – 2007 : V2.1 .2/ EN 301 489 – 3 : 2002 V1.4.1 / CE
<b>RoHs</b>	Yes

## HOUSING

---

<b>Dimensions</b>	180 x 110 x 90 mm
<b>Waterproof grade</b>	IP65
<b>Materials</b>	ABS light gray - 4 hole partitioned fixing
<b>Operating temperature</b>	-25°C to +60°

## MECHANICAL DRAWINGS

---

